



- Notes :-
1. All metal parts to be Mild Steel Grade 43C, hot-dip galvanised to BS EN ISO 1461. Welds to be 5mm to BS EN 1011-2; surface welds to be cleaned flush.
 2. Main dimensions are for 1800mm high fence. Dimensions in brackets are for 2400mm high fence.
 3. Fence to be in accordance with BS 1722-12 (Type SP18 or SP24).
 4. 1800mm high fence to have one intermediate support at mid-point of panel, 2400mm high fence to have two intermediate supports at third-points.
 5. Fishplates to be 6mm thick, connected with 12mm dia. bolts, to BS 1722-12.
 6. See Appendix 3/1 and 19/5 for painting requirements.
 7. Non-Standard and end panels shall be fabricated after measurement on site if necessary.
 8. All dimensions in millimetres.



SCHEME
STANDARD DETAIL SHEETS



DRAWING
CORRUGATED ANGLE
PALE FENCE
(1.80 OR 2.40 METRES HIGH)

This detail is controlled by Birmingham City Council. Email - Transport.Projects@Birmingham.gov.uk

DATE	REV.	DETAILS & FRAME AMENDED	DH	PP
2013	D	DETAILS & FRAME AMENDED	DH	PP
2009	C	NOTES AMENDED	PAS	TE
2004	B	NOTES AMENDED	-	AJC
2002	A	BORDER & TITLE AMENDED	-	AJC
2000	-	ORIGINAL DRAWING CREATED	SRE	AJC

DATE	REV.	DESIGNER	PM	PP	DRN	PM	REVISION
DH	03/12/13	TE	03/12/13	PP	03/12/13		D

DWG. No
HW/3.03

DRAWING STATUS
GENERAL

SCALE
1:20

