

- Notes :-**
1. Fine sawn York Stone paving, gauge varies in random lengths. 65-75mm thickness. Natural colour either butt joint or 10mm joint filled with Class 1 mortar bucket handle finish.
  2. All dimensions in millimetres.
  3. Joints to be filled with approved sealant (Easyflow)
  4. Existing kerb face to be broken out to allow a minimum of 100mm concrete under the stretcher course.



STANDARD DETAIL SHEETS

TYPICAL YORKSTONE PAVING DETAIL




This detail is controlled by Birmingham City Council. Email - Transport.Projects@Birmingham.gov.uk

DATE	REV.	DESCRIPTION	BY	CHKD
2014	F	DETAILS AMENDED	DH	PP
2013	E	DETAILS & FRAME AMENDED	DH	PP
2004	D	NOTES AMENDED	CCH	MM
2004	C	NOTES AMENDED	-	AJC
2003	B	NOTES AMENDED	-	BSK
2002	A	DETAILS & NOTES AMENDED	-	AJC
2000	-	ORIGINAL DRAWING CREATED	MP	AJC

DATE	REV.	DESCRIPTION	BY	CHKD
2014	F	DETAILS AMENDED	DH	PP
2013	E	DETAILS & FRAME AMENDED	DH	PP
2004	D	NOTES AMENDED	CCH	MM
2004	C	NOTES AMENDED	-	AJC
2003	B	NOTES AMENDED	-	BSK
2002	A	DETAILS & NOTES AMENDED	-	AJC
2000	-	ORIGINAL DRAWING CREATED	MP	AJC

DWG. No  
HW/11.52



A3

1 2 3 4 5 6 7 8

1 2 3 4 5 6 7 8

A

A

B

B

C

C

D

D

E

E

F

F