



1. CLEARANCE FOR 30 M.P.H.

2. CLEARANCE FOR 40 M.P.H.

ROADS RESTRICTED TO 30 M.P.H.

0.45m minimum clearance for road signs, guard rail and lighting columns.

Minimum horizontal clearance should be measured at a height of 3.0m above carriageway.

ROADS WITH A SPEED LIMIT OF 40 M.P.H.

0.60m minimum clearance for road signs, guard rail and lighting columns.

- Notes :-
- Individual lighting column locations are to be specified in lighting schedule.
 - Clearance distances as above to be maintained between sign face edge and / or posts (whichever is nearest to kerb edge) and kerb face.



SCHEME
STANDARD DETAIL SHEETS



DRAWING
MINIMUM CLEARANCES FROM EDGE OF CARRIAGEWAY

This detail is controlled by Birmingham City Council. Email - Transport.Projects@Birmingham.gov.uk

DATE	REV.	DESCRIPTION	BY	CHECKED
2013	E	DETAILS & FRAME AMENDED	DH	PP
2010	D	DETAILS & NOTES AMENDED	CCH	MM
2003	C	NOTES AMENDED	-	AJC
2002	B	NOTES AMENDED	-	AJC
2001	A	NOTES AMENDED	-	AJC
2000	-	ORIGINAL DRAWING CREATED	SRE	AJC

DATE	DESIGNER	PM	PP	SCALE
DRAWN	DH	TE	PP	E
DATE	12/12/13	12/12/13	12/12/13	
DRAWING STATUS	GENERAL			NTS

DWG. No
HW/13.03